

Gestetner

Productive and affordable 1200 dpi output



L A S E R P R I N T E R

P7016



P7016

1200 DPI
LASER PRINTER



EXPECT BIG THINGS...

from the Gestetner P7016 Network Printer. Its 16 PPM print speed, true 1200 dpi laser output and versatile paper-handling capabilities will impress even the most demanding member of your workgroup or small office.

FULL-SIZE PERFORMANCE

- A compact footprint ensures that the Gestetner P7016 will fit virtually anywhere.
- Front access means that you can do everything – including adding paper and changing cartridges – from the front of the printer.
- Consumable replacement is a simple task with the P7016's All-In-One-Cartridge system. It also reduces consumable inventory and contributes to the P7016's overall low cost of ownership.
- Busy workgroups and offices will appreciate the sophistication of the P7016's paper handling capabilities. Up to 850 sheets of paper from three sources can be available at all times. Plus, an optional Envelope Feeder ensures that your envelopes look as good as the documents inside.

WORKS ON YOUR NETWORK

- The Gestetner P7016's powerful 133 MHz RISC processor drives maximum output efficiency.
- First Print Speed of 11 seconds or less boosts productivity on short run jobs.
- An optional Network Interface Card supports Fast Ethernet and AppleTalk LAN connections and provides seamless integration with today's most popular network platforms – including Windows® 2000.
- PCL6 and Adobe PostScript 2 mean out-of-the-box compatibility with most business software, and Auto Emulation Switching eliminates costly printing errors.
- Proprietary Gestetner Net Vision Software makes it easy to install and monitor your Gestetner P7016, or any Gestetner connected system, on your network – whether it's Client/Server or Peer-to-Peer. An icon on the Windows® Task Bar, Net Vision allows you to “see” how your P7016 is performing at all times.

EXPECT MORE FROM GESTETNER

Today, choosing the right network output system is challenging but Gestetner consultants can make it easy. So, whether your network output needs are for black and white...color...multifunctional... or a combination of all three, Gestetner has an answer.

For more information about the Gestetner P7016 Network Printer, contact your authorized Gestetner sales location.

www.gestetnerusa.com

Printer Specifications

| | |
|--------------------|--|
| Technology | Laser |
| Resolution | 1200/600/300 dpi |
| Throughput | 16 ppm letter |
| First Print Time | Less than 11 seconds |
| Weight | 26.41 lbs. |
| Dimensions (WxDxH) | 14.2" x 16.6" x 10.6" |
| Input Capacity | 250 sheets + 100 sheet Multi-Tray (8.5" x 14" max.); 1 optional 500 sheet 8 1/2" x 11" Max. Tray; Optional envelope feeder installed in optional (Ltr.) paper tray |
| Output Capacity | 250 sheets |
| Paper Size | 3.88" x 5.83" – 8.5" x 14" |
| Paper Weight | Standard/Optional Trays 16 - 24 lbs. Standard Multi Tray 14 - 42 lbs. |
| Warm-up Time | 39 seconds or less |

Energy Star Tier 2 Specifications

| | |
|-----------------------------|--------------------------------------|
| Rating Power Specifications | 120V, 60 Hz |
| Emi | FCC Class B, DOC |
| Sound Level | Standby - 48 db Operating - 59 db |
| Safety Standard | UL1950, CSA950 |

Controller Specifications

| | |
|--------------------|--|
| Printer Language | PCL5e, PCL6 & PS Level 2 |
| Fonts | 35 Intellifont, 10 TrueType Fonts, 1 Bitmap Font, 35 Type 1 Fonts |
| Memory | 16 MB SDRAM, expandable up to 80 MB |
| Hard Disk | Optional 1.6 GB |
| CPU | NEC R4310 133 Mz RISC Processor |
| Driver | PCL5e & PCL6: for Win 3.1x/95/98/2000, Win NT 4.0 PS Level 2 PPD file: for Win 95/98/2000, NT 4.0 & MAC OS 7.5 or later |
| Interface | Standard Bi-directional IEEE1284; Optional RS232C; Optional Network Interface Card 10 BaseT/100 BaseTX |
| Network Protocol | Optional NIC supports TCP/IP, IPX/SPX, EtherTalk (AppleTalk) |
| Utility Management | Net Vision included for Win 95/98/2000 & Win NT 4.0; Controller supports SNMP - MIBII & industry standard MIB (RFC1759) |

Gestetner

