

Gestetner

High-performance, productive and compact laser printers



DESKTOP LASER PRINTERS

P7325/P7325n

YOU'LL LIKE THE WAY THEY WORK ON YOUR NETWORK

Whether you're printing general office correspondence, spreadsheets, invoices or electronic forms, the Gestetner P7325/P7325n excel at meeting your daily printing needs. Blending high-performance printing capabilities, a variety of network connection choices and professional image quality, the P7325/P7325n are certain to be welcome additions to busy office and workgroup environments.



P7325/P7325n

DESKTOP LASER PRINTERS

PEOPLE-FRIENDLY

The P7325/P7325n make it easy for everyone in your office to be more productive.

- Keep PC, Macintosh and UNIX users happy with the P7325/P7325n's multiple print drivers, including RPCS (Refined Printing Command Stream), PCL 5e/6 emulation, Adobe® PostScript® 3™ and PDF Direct Print.
- Enjoy optimized printing performance with a fast 7.5 second first print speed and 26 ppm continuous print speed.
- Add the optional hard disk drive and gain the benefits of Multiple Original Set Printing, Sample Print, Locked Print and Font Download.
- Lighten the workload for your IT personnel with intelligent print management utilities that enable remote monitoring and management of the P7325/P7325n via a standard Web Browser. And, automatic e-mail alerts provide "real time" operating status, which significantly reduces downtime.
- Access to a variety of intelligent paper-handling features – including optional duplex printing and a generous paper capacity of up to 1,600 sheets – ensures that you'll power through print jobs.

NETWORK-FRIENDLY

Getting the P7325/P7325n on your network is an exercise in choice.

- Connect to your network right out of the box with the P7325n's standard Ethernet Interface (optional for the P7325).
- Enable field personnel, vendors or clients to connect directly to the P7325/P7325n via a standard bi-directional parallel port – no network login required.
- Speed print jobs across the network and free up valuable bandwidth with the optional IEEE 1394 interface.
- Position your P7325/P7325n where you need it most and eliminate the constrictions of physical cables with one of two Wireless LAN interface options – IEEE 802.11b or Bluetooth.

OFFICE-FRIENDLY

Put the P7325/P7325n to work and you'll see productivity rise while operating costs decline. For more information about the Gestetner P7325/P7325n network printers, contact your authorized Gestetner dealer.

www.gestetnerusa.com



Gestetner

Gestetner Stamford, Connecticut 06904

Windows® and Windows® 95/98/Me/NT 4.0/2000/XP are registered trademarks of Microsoft Corporation. Macintosh®, Mac OS and AppleTalk® are registered trademarks of Apple Computer, Inc. Adobe® and PostScript® are registered trademarks of Adobe Systems, Inc. PCL® is a registered trademark of Hewlett-Packard Company. All other trademarks are the property of their respective owners. Product specifications and external appearances subject to change without notice. Print speed may be affected by network, application or PC performance. Products may be shown with optional features accessories. For maximum performance and yield, we recommend using genuine Gestetner parts and supplies.

♻️ Printed in U.S.A. on recycled paper. (G1862) 25M 9/03



General Specifications

Configuration	Desktop
Print Technology	Electrophotographic laser, dual component toner
Print Speed (Letter)	26 ppm (1200 x 1200 dpi)
First Print Speed	7.5 seconds or less
Warm-up Time	Less than 19 seconds
Resolution	1200/600/300 dpi
Maximum Duty Cycle	Up to 150,000 pages per month
Dimensions (W x D x H)	15.3" x 17.7" x 13.6"
Weight	37.5 lbs.

Paper Handling Specifications

Input Capacity	Standard Configuration: 500 sheets, plus Bypass Tray (100 sheets or 10 envelopes) Maximum Paper Input Capacity: 1,600 sheets/4 sources
Output Capacity	250 sheets
Duplex Printing	Optional
Paper Size	Standard Tray: 8.5" x 11", 8.5" x 14", 5.5" x 8.5" Standard Bypass Tray: Width 3.5" to 8.5"; Length 5.5" to 17"
Paper Weight	Standard Tray/Optional Paper Feed Unit: 16 - 28 lb. Bond Standard Bypass Tray: 16 lb. Bond - 90 lb. Index
Paper Type	Plain paper, recycled paper, envelopes, laser-quality qualified transparencies and labels

Controller Specifications

CPU	TX4955 300MHz
Memory	64 MB; 320 MB maximum
Hard Disk Drive	Optional
Printer Languages	PCL 5e/6 emulation, Adobe PostScript 3, RPCS (Refined Printing Command Stream) and PDF Direct Print
Fonts	PCL: 35 Intellifonts, 10 TrueType, 1 bitmap; PS: 136 Type 1 fonts
Printer Drivers	PCL 5e/6: Windows 95/98/Me/NT 4.0/2000/XP/Server 2003 PS: Windows 95/98/Me/NT 4.0/2000/XP/Server 2003; Mac OS (8.6.0 or later); Mac OS X (10.1.x or later) RPCS: Windows 95/98/Me/NT 4.0/2000/XP/Server 2003
Standard Interfaces	P7325: Parallel, USB 1.1/2.0 P7325n: 10/100 BaseTX Ethernet, Parallel, USB 1.1/2.0
Optional Interfaces	10/100 BaseTX Ethernet (P7325 only), IEEE 1394, IEEE 802.11b Wireless LAN, Bluetooth Wireless
Utilities	SmartNetMonitor; Web SmartNetMonitor; Web Image Monitor (embedded to NIC); DeskTopBinder Lite; Plug-In to HP Web JetAdmin; Plug-In to HP OpenView, CA Unicenter and IBM Tivoli NetView; Printer Utility for Mac; and Font Manager 2000.

Paper Handling Options

Paper Feed Unit Type 400*

Paper Size	8.5" x 11", 8.5" x 14", 5.5" x 8.5"
Paper Weight	16 - 28 lb. Bond
Paper Capacity	500 sheets

*P7325/P7325n can accommodate up to two additional Paper Feed Units.

Envelope Cassette Type 400*

Paper Size	Com10, Monarch, C5, C6, DL
Capacity	60 envelopes

*One Optional Paper Feed Unit is required for the Envelope Cassette. High quality envelopes are recommended.

Duplex Unit AD450

Paper Size	8.5" x 11", 8.5" x 14", 5.5" x 8.5"
Paper Weight	17 - 28 lb. Bond

Interface Options

Network Interface Board Type 2610*

Topology	10/100 BaseTX Ethernet (Auto Sensing)
Network Protocols	TCP/IP; IPX/SPX; NetWare 3.11/4.1 or above, 5.0/5.1/6.x; AppleTalk; NetBEUI; IPP (Internet Printing Protocol)
Other Supported	UNIX* (lpr/lpd): Sun Solaris 2.6/7/8/9; HP-UX 10.x/11.x; SCO OpenServer 5.x; Red Hat Linux 6.x/7.x; IBM AIX 4.3/5L V5.1

*For UNIX support, visit www.gestetnerusa.com/download

*Standard for P7325n. Cannot be used in conjunction with IEEE 802.11b interface.

IEEE 802.11b Wireless LAN Interface Type A*

Data Transmission Speed	1/2/5.5/11 Mbps
-------------------------	-----------------

*Cannot be used in conjunction with 10/100 BaseTX Ethernet.

Bluetooth Interface Board Type 2045

Data Transmission Speed	1 Mbps
-------------------------	--------

IEEE 1394 Interface Board Type 4510*

Cables (Included)	2.0m 6-pin to 6-pin cable, 2.0m 6-pin to 4-pin cable
Hardware Specifications	6 pins; 2 ports available
Data Transmission Speed	400/200/100 Mbps
System Requirement	Windows 2000 Professional/Server with Service Pack 1 Windows XP for IP over IEEE 1394 (TCP/IP Protocol)

Memory Options

Hard Disk Drive Type 2600*

*HDD is required for the Locked Print (Secure Printing), Sample Print, Collation, Job Spooling, permanent font downloading.

64 MB/128 MB/256 MB Memory Module*

Hardware Specifications	144-pin DIMM SDRAM (PC133 compliant)
-------------------------	--------------------------------------

*Additional Memory Module is recommended to duplex print (two-sided) at the highest (1200 dpi) resolution.