

Gestetner

An Affordable, Best-In-Class Network Printer



NETWORK LASER PRINTER

P7535n



Standard 250-Sheet Face-Down Output Tray

Standard 100-Sheet Bypass Tray

Standard 500-Sheet Tray

Optional 500-Sheet Tray*

Optional 500-Sheet Tray*

*Add two 500-sheet trays to take your total paper capacity to 1,600 sheets.

Cost Efficiency Without Compromise

THE POWERFUL GESTETNER P7535n PUTS THE WORD “WORK” IN THE PHRASE “WORKGROUP PRINTER”. DESIGNED TO KEEP YOUR BUSINESS RUNNING SMOOTHLY, THE P7535n OFFERS AN IMPRESSIVE ARRAY OF MUST-HAVE FEATURES — A FAST PROCESSOR, LARGE EXPANDABLE PAPER SUPPLY, WEB-BASED MANAGEMENT, ADVANCED SECURITY AND FLEXIBLE PRINT DRIVERS. FROM TOP TO BOTTOM, THE VALUE-PACKED P7535n EARNS ITS KEEP.

ADVANCED PERFORMANCE

Quick job turnaround is standard operating procedure with the Gestetner P7535n’s fast 35 page-per-minute print speed, and swift 6.5-seconds first-page-out time. Even when in Energy-Saver mode, a quick 12-second recovery ensures rapid job turnaround. And, with the P7535n’s high 200,000-page duty cycle, you’re assured that this workhorse printer will reliably handle your heaviest print volumes.

WHEN APPEARANCES COUNT

The Gestetner P7535n always makes a great impression, con-

sistently producing crisp, clear text, graphics and photos, with up to 1200 x 1200-dpi resolution. When appearances count, you can count on Gestetner.

CONNECTS YOUR WAY

Hassling with tangled wires is a thing of the past with IEEE 802.11b or Bluetooth wireless LAN interface options, which free laptop users (with a wireless interface card) to print directly to the P7535n. The IEEE 1394 interface option boosts data transfer rates up to 400Mbps, conserving valuable bandwidth by reducing network traffic.



Print at 35 pages per minute with a 6.5 seconds first page output time.

Parallel Printing



ERGONOMIC DESIGN

With no side trays to get in your way, paper refills, toner cartridge changes and routine maintenance is a snap thanks to the Gestetner P7535n's front-access design. Space-saving and compact, the sleek P7535n is the perfect fit for tight spaces, even when fully configured with optional trays.



The optional Duplex Unit cuts paper usage and filing space requirements in half.



With the convenient All-In-One Cartridge, you no longer need to purchase and store separate consumable items.

LETTER-TO-LEDGER PAPER HANDLING

The Gestetner P7535n's generous 600-sheet standard paper capacity, which includes a standard 500-sheet paper supply and versatile 100-sheet multipurpose bypass, can be expanded to 1,600 sheets via 500-sheet Paper Feeder Unit options, further minimizing workflow interruptions. The fully enclosed, front-loading universal tray holds paper sizes up to 11" x 17". Or, use the bypass to print onto a wide range of media types, including transparencies, card stocks, recycled papers, or up to 10 envelopes.

MONEY AND TIME-SAVING OPTIONS

The optional stackless Duplex Unit automatically prints your reports, contracts and letters on two sides of the page, at nearly the same speed as one-sided printing. You'll cut paper usage and filing space requirements in half, increasing your cost savings. And the optional 60-Envelope Cassette saves time by automating this labor-intensive task.



Print envelopes and quickly change paper sizes with easy-to-use paper guides.

INSTANT ROI UTILITIES

Exceptional return-on-investment is yours with intuitive desktop utilities that make the monitoring and management of network devices fast and easy. Remotely check paper/toner supply, job data, on-line status,

and more...from anywhere, at any time, using Web- and PC-based software tools...

Web Image Monitor allows for convenient desktop management of individual P7535n printers installed on the network, via a standard Web browser. Even receive instant e-mail alerts.

SmartDeviceMonitor enables intuitive desktop monitoring, management and configuration. Use Recovery Print to ensure that documents print without delay by redirecting print jobs from the default printer to an alternate printer. Parallel Print leverages capacity of multiple network printers to create sets of a single document; three networked P7535n printers have the virtual speed of 105 ppm!

And, bundled DeskTopBinder Lite, a versatile document management application, allows users to search, view, print, organize, and combine documents, even those created in different applications.

SAFEGUARD PRINT DATA

Gestetner has developed a comprehensive suite of security solutions that safeguard your valuable information assets.

Print Data Encryption via Internet Printing Protocol (IPP) uses Secure Sockets Layer/Transport Layer Security (SSL/TLS) to scramble communication between the computer and P7535n, thwarting attempts to access sensitive data.

Locked Print prevents others from reading or removing documents sitting on the P7535n's exit tray by suspending output until a PIN is entered at the control panel (requires optional Hard Disk Drive).



The optional Network Data Protection Unit module provides another level of security by allowing only the P7535n to recreate the data stream.

Compliance with rigorous federal regulations governing the privacy of printed and electronic data is another reason why Gestetner security solutions should be a part of your strategy to address ongoing information security challenges.

DESIGNED TO DELIVER

Getting more from your investment in advanced technology has just gotten easier...the Gestetner P7535n, with seamless network integration, Web-based management tools, competitive hardware cost, low cost of operation, and an abundance of productivity-enhancing features make this printer a smart business decision.

For more information, contact your authorized Gestetner Dealer.

www.gestetnerusa.com

P7535n

System Specifications

Configuration	Desktop
Technology	Laser-beam scanning, electro-photographic printing with dual-component toner development
Resolution	PCL5e: 300 x 300, 600 x 600-dpi PCL6: 600 x 600, 1200 x 1200-dpi RPCS: 300 x 300, 600 x 600, 1200 x 1200-dpi PS3: 600 x 600, 1200 x 1200-dpi
Printing Speed	35 ppm
Duplex Speed	Approximately 100% productivity of simplex speed
First Print Speed	6.5 seconds or less
Dimensions (WxDxH)	18.8" x 17.2" x 13.5" (478mm x 437mm x 343mm)
Weight	44 lbs. (20 kg)
Warm-up Time	Less than 19 seconds
Power Source	120 V, 60Hz
Power Consumption	850W or less
Energy Saver Mode	5.5W or less
Paper Capacities	Up to 1,600-sheet total capacity Standard Tray: 500 sheets Standard Bypass Tray: 100 sheets Optional Paper Tray: 500 sheets (1 or 2 may be added)
Output Capacity	250 sheets face down
Paper Sizes	Standard/Optional Trays: 8.5" x 11", 8.5" x 14", 11" x 17", A4, A3 Bypass: Width 3.5" to 12" (90 – 305mm); Length 5.8" to 17" (148 – 432mm)
Paper Weight	Standard/Optional Trays: 16 – 28 lb. bond (60 – 105 g/m ²) Bypass: 14 lb. bond – 43 lb. bond/90 lb. index (52 – 162 g/m ²)
Acceptable Paper Types	Plain paper, recycled paper, envelopes*, and laser qualified transparencies** *Through Bypass Tray or optional Envelope Cassette. **Through Bypass Tray.
Safety Regulations	UL UL60950, FCC Part 15 Class B

Controller Specifications

CPU	TX4955 @ 372MHz
Printer Languages	PCL 5e/6 emulations; Adobe PostScript 3; Ricoh RPCS; PDF
Fonts	Adobe PostScript 3: 136 Type 1 fonts PCL: 35 Intellifonts; 10 TrueType fonts; 1 bitmap font
Memory	128MB RAM standard; Up to 256MB RAM maximum; 20GB Hard Disk Drive (optional)
Standard Interfaces	10/100BaseTX Ethernet; Bi-directional IEEE 1284 Parallel; USB 1.1/2.0
Optional Interfaces	IEEE 802.11b wireless LAN; Bluetooth wireless; IEEE 1394 *Only one additional interface can be installed.
Network Protocols	TCP/IP, Novell IPX/SPX, IPP, AppleTalk, SMB/NetBEUI
Drivers	PCL 5e/6 & Ricoh RPCS: Windows 95/98/Me/NT4.0/2000/XP/Server 2003; Adobe PostScript 3: Windows 95/98/Me/NT4.0/2000/XP/Server 2003; Mac OS (8.6 or later); Mac OS X (10.1.x or later) UNIX: Solaris, HP-UX, Red Hat Linux, SCO, IBM AIX
Driver Functions	User codes 400, watermark, form overlay, toner save, rotate print, poster, duplex ¹ , cover sheet, slip sheet, booklet, orientation, layout (n-up), reduce/enlarge, centering, sample print ² , locked (secure) print ² , job spooling ² , collation ² , font downloading ² ¹ Requires optional Duplex Unit ² Requires optional Hard Disk Drive
Software Utilities	SmartDeviceMonitor for Administrator and Client; Web SmartDeviceMonitor; Web Image Monitor; DeskTopBinder Lite; Printer Utility for Mac; Agfa Font Manager 2000

Controller Specifications (cont.)

Controller Features	Rendezvous Support: Apple's version of Zero Configuration Networking, is a standard utility that enables the P7535n to automatically recognize and connect with other devices on an IP network; no special setup or configuration is required. PDF Direct Print: Enables a user to send PDF print jobs directly to the P7535n without requiring access to Acrobat Reader. Dynamic DNS: Automatically updates the P7535n's IP address and host name when the printer is powered on.
----------------------------	---

Controller Options

20GB Hard Disk Drive Type 2600
IEEE 1394 Interface Board Type 4510*
IEEE 802.11b Wireless LAN Interface Type F*
Bluetooth Interface Board Type C*

*Only one additional interface can be installed.

Memory Options*

144-pin DIMM SD-RAM (PC133 compliant)
256MB RAM Memory Unit Type C

*Additional Memory Module is recommended to duplex print (two-sided) at the highest (1200 dpi) resolution.

Security Features

Network Data Protection Unit (DESS) Type B
Enables data encryption so that only the printer can properly recreate the data stream, guarding against information theft.
Other Security Features
SNMP v3 Authentication and Privacy Encryption (password/print data encryption); PDF Direct Print Password Protection; Locked (Secure) Print*; User Codes

*Requires optional HDD.

Optional Paper Handling Accessories

Paper Feed Unit Type 610	
Paper Size	8.5" x 11", 8.5" x 14", 11" x 17", A4, A3
Paper Weights	16 – 28 lb. bond (60 – 105 g/m ²)
Paper Capacity	500 sheets; 1 or 2 units may be added
Duplex Unit AD 610	
Paper Size	8.5" x 11", 8.5" x 14", 11" x 17", A5, A4, A3
Paper Trays	All, including Bypass Tray
Paper Weight	17 – 28 lb. bond (64 – 105 g/m ²)
Envelope Feeder Type 610*	
Paper Size	Com10, Monarch, C5, C6, DL
Paper Weight	19 – 24 lb. (72 – 90 g/m ²)
Capacity	60 envelopes

*One optional Paper Feed Unit is required for the Envelope Cassette. High quality envelopes are recommended.

Consumables*

Toner Type 115 Black	20,000 pages @ 5%
Maintenance Kit Type 610	Yield – 90,000 pages (Includes: Fusing Unit, Transfer Roller, Paper Feed Roller)

*P7535n ships with starter toner cartridges at 6,000 pages @ 5% coverage; all other consumables ship at full yield.

Gestetner



Gestetner Five Dedrick Place, West Caldwell, NJ 07006

GESTETNER® is a registered trademark of Ricoh Corporation. Windows® and Windows® 95/98/Me/NT4.0/2000/XP/Server 2003 are registered trademarks of Microsoft Corporation. Macintosh®, Mac® OS and AppleTalk® are registered trademarks of Apple Computer, Inc. Adobe® and PostScript® are registered trademarks of Adobe Systems, Inc. PCL® is a registered trademark of Hewlett-Packard Company. RPCS™, SmartDeviceMonitor™, DeskTopBinder™ and Web Image Monitor™ are trademarks of Ricoh Company, Ltd. All other trademarks are the property of their respective owners. Product specifications subject to change without notice.

♻️ Printed in U.S.A. on recycled paper. (G2077) 20M 3/05